

9" Ergo Crimp

Higher Performance
Superior Comfort
Reliability



The next generation of crimp tool technology designed around the user. Crimping is even easier and more comfortable. The “straight plate” lower jaw assembly eliminates critical structural stress points, common in most competitive tools - it will not break under heavy stress and will last for years to come. Higher performance, reliability and comfort, it’s all here.

- Reduced handle grip distance makes it ideal for all hand sizes and allows for prolonged, comfortable use
- Smooth triple ratchet design eliminates breakover hand force
- Adjustable cam allows precision ratchet adjustment for a perfect crimp, no matter the die set or application
- Accepts crimp die sets from most other popular tools. Your old crimping dies will work!
- Built-in safety release


Technical Data

- Length: 9" (229mm)
- Weight: 16oz (454g)

Ordering Information

Description	P/N	UPC CODE
9" Ergo Crimp Tool, Frame Only	16500C	849160006664

See Die Sets
and More



Phone: 800.749.5783
Fax: 800.749.5784
California, USA

www.platinumtools.com

We Make Connections EZ!

9" Ergo Crimp Tool Dies and Applications



Die	Crimp	Part # Tool & Die / Die Only	Cable Types	Crimp Type/Sizes	Connector Types
		16501C / 17051C	22-10 AWG Solid or Stranded	3 Cavity 22-18 AWG (.34-.75 mm ²) 16-14 AWG (1.5-2.5 mm ²) 12-10 AWG (4-6 mm ²)	Heavy Duty Insulated Terminals and Lugs
		16502C / 17052C	22-8 AWG Solid or Stranded	4 Cavity 22-18 AWG (.34-.75 mm ²) 16-14 AWG (1.5-2.5 mm ²) 12-10 AWG (4-6 mm ²) 8 AWG (10 mm ²)	Non-Insulated Terminals
		16503C / 17053C	RG-59/6 Belden 8281/1694A	Hex .042 / .068 / .255 / .324	BNC, TNC, HDTV
		16504C / 17054C	RG-58, RG-59, RG-62	Hex .068 / .213 / .255	BNC, TNC 3 Piece
		16505C / 17055C	RG-59, RG-6	Hex .256 / .315 / .346	F Type, 1 & 2 Piece CATV
		16506C / 17056C	RG-6, RG-6 Quad 8281, 1694A, 1695 1505, 9259, 9231	Hex .360 / .324 / .068	BNC, TNC, F Type
		16507C / 17057C	22-10 AWG Solid or Stranded	3 Cavity 22-18 AWG (.34-.75 mm ²) 16-14 AWG (2.5-1.5 mm ²) 12-10 AWG (4-6 mm ²)	Standard Duty Commercial Insulated Terminals & Lugs
		16508C / 17058C	22-10 AWG Stranded	3 Cavity 22-18 AWG (.34-.75 mm ²) 16-14 AWG (2.5-1.5 mm ²) 12-10 AWG (4-6 mm ²)	Commercial Pin & Socket Type Contacts, Open Barrel Contacts, Box Contacts
		16509C / 17059C	RG-174, 187, 188, 316 Mini Coaxial	Hex .178 / .128 / .068	SMA, SMB, Mini 59, BNC, TNC, Mini UHF
		16510C / 17060C	RG-8, RG-11, RG-213, RG-214, LMR400	Hex .429 / .100 / .080	N Type Plugs
		16511C / 17061C	RG-59/62, 734, 735, RG-6	Hex .311 / .256 / .200 / .068 / .039	HDTV, True 75 Ohm BNC, TNC



Contact us about custom dies.

Description	P/N	UPC CODE
Quick Change Die Screws, Set of 2	17099C	849160000617

